



# User Manual Mini Crosser X2

Serial number: \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_

Delivery date: \_\_\_\_\_ Year 20\_\_\_\_\_

**This vehicle was supplied by:**

**Date:** / /

**Dealer:**

For this product You can expect to find the following documentation:

- User manual
- Service manual
- Spare parts list
- Presell information.

### **Medema A/S**

Enggårdvej 7  
Snejbjerg  
DK-7400 Herning  
Denmark

Telefon: 70 10 17 55  
Mail: [info@medema.com](mailto:info@medema.com)

---

## Contents

Intended occupant.....	5
Help for the visually impaired .....	5
FSN (Field Safety Notice).....	5
Symbols.....	6
Warning! .....	6
Alarm .....	6
Contagion!.....	6
Introduction.....	7
Declaration of conformity.....	8
Medema A/S Warranty .....	9
Control panel .....	10
User menu.....	11
Programming the User Menu .....	14
Preparations / Adjustments prior to use .....	16
Electric seat adjustment .....	18
Seat rotation.....	19
Steering column .....	20
Serial number.....	21
Driving the Mini Crosser X2 .....	22
Lap belt.....	25
Specific driving situations.....	27
Long hills/difficult ground .....	29
Anti-tilt wheels / stabilisers .....	30
Cleaning .....	30
General care and maintenance .....	31
Insurance.....	32
Batteries .....	33
Battery weight.....	33
Charging.....	33
Battery disposal.....	35
Standby power.....	35
Storage .....	37
Changing the wheels.....	38
Fuses .....	43
Brakes.....	44
Disengagement.....	45
Transporting by motor vehicle .....	46
Securing to vehicle floor with belts .....	47
Transporting by plane .....	50
Towing .....	50
Dimensioned drawing, Mini Crosser X2 3W.....	51
Dimensioned drawing, Mini Crosser X2 4W.....	52
Introduction to the Ergo2 seat .....	53
Basket in front .....	57

<b>Basket on seatback .....</b>	<b>58</b>
<b>Introduction to the Eblo seat.....</b>	<b>59</b>
<b>Flame resistance .....</b>	<b>60</b>
<b>Troubleshooting .....</b>	<b>61</b>
<b>Technical data.....</b>	<b>64</b>
<b>Weight of the seats.....</b>	<b>67</b>
<b>Programming .....</b>	<b>67</b>

## Intended occupant

The intended occupant of the Mini Crosser X is a person with limited ability of walking themselves.

The occupant must be able to see in order to register traffic signals and other road users when driving in traffic. The occupant can be deaf and/or speechless.

The occupant must have a cognitive ability to understand the operation of a scooter and its buttons and icons.

The Mini Crosser can be driven with only one hand either left or right.

The maximum occupant weight is 175 kg.

---

## Help for the visually impaired

If you have difficulty reading small print in the user manual, we recommend that you visit our website, where you can read this manual in PDF format. You can enlarge the PDF manual on your PC monitor to suit your needs and preferences.

If you find it difficult to understand the manual and have general questions about the product, please feel free to contact us. You can find our contact info on page two in this user manual.

You can find manuals for all our products on our web page [www.medema.dk](http://www.medema.dk). Or contact Medema A/S, and we can send the manuals in a mail for you. Find the contact information on page two in this manual.

---

## FSN (Field Safety Notice)

All information concerning safety can be found at [www.medema.com](http://www.medema.com), which is always updated with the latest safety information. In the event of important safety-related changes, we will notify our customers directly (FSN).

---

## Symbols



Used in the manual to indicate sections describing situations where extra care is required owing to the risk of personal injury.



Used to indicate sections on electromagnetic compatibility (EMC).

---

## Warning!



For safety reasons the vehicle must not be lent to persons who are not completely familiar with it. The vehicle is designed for one person only.



The Mini Crosser X2 has been designed for users weighing max. 175 kg including any accessory added to the vehicle. Can be supplied in a HD version as standard for a max user weight of 250 kg including any accessory added to the vehicle.

---

## Alarm

Temperature sensor, alarm system and tilt alarm are built into the same box that can be acquired as an option for the Mini Crosser X2.

### Note!



The alarm is always turned off on delivery. See the chapter about "Programming the User Menu" to turn on the alarm.

---

## Contagion!

A standard Mini Crosser is equipped with tyres that does not contage, but if another type of tyres are used, it can sometimes rub off on floor coverings, particularly linoleum. Medema A/S assumes no responsibility in case of contagion.

To prevent this, we recommend that you protect delicate floors with some sort of driving surface.

---

## Introduction

Congratulations on your new Mini Crosser X2 electric mobility Mini Crosser.

You have now taken possession of an electric mobility Mini Crosser developed for outdoor driving by active users. It is what is called a Class C vehicle in according to the European standard EN 12184.

For optimum enjoyment of this vehicle - and to avoid breakdowns and accidents - we recommend that you read this User Manual carefully. As a new user, you should pay particular attention to the section entitled "Driving the Mini Crosser X2".

The Mini Crosser X2 is designed for safe travel for at least 10 years, up to a max. of 5,000 hours, providing it has service and safety inspections every third year, which is equivalent to around 1500 hours of operation. The service must be carried out by an authorised workshop.



**IMPORTANT!** For safety reasons it is of the outmost importance that service and safety check intervals are complied with, as this minimises the risk of brake failure and short-circuits in the wiring, which could generate heat and cause a fire.

We offer a wide range of accessories for the Mini Crosser X2 that can make everyday life easier for you. You are always welcome to contact us for further information on special accessories and adaptations.

Medema A/S is not responsible for any damage or injuries caused by inappropriate or unsafe use of the Mini Crosser X2.

If you have any further questions about the Mini Crosser X2 or this User Manual, you are always welcome to get in touch. Our contact details are as follows:

### **Medema A/S**

Tel: +45 7010 1755

Email: [info@medema.com](mailto:info@medema.com)

Internet: [www.medema.com](http://www.medema.com)

NB: Errors and omissions excepted. We reserve the right to update this manual as required.

---

## CE Declaration of conformity

Model: Mini Crosser X2

Medema-A/S declares on our sole responsibility that the product range mentioned below are manufactured in accordance with our incorporated standards and are in conformity with the following directives and standards if they are used according to our instructions:

Regulation (EU) 2017/745 of the European Parliament and of the Council of 5 April 2017 on medical devices.

EN 12184:2014 Electrically powered wheelchairs, scooters and their chargers - Requirements and test methods

Risk analysed according to ISO 14971:2012, Medical devices – Application of risk management to medical devices.

Type of use : Transporting walking disabled people  
 Risk Class : I

The product range in the Mini Crosser model-X2 includes the following items

Product name	Basic UDI-DI
Mini Crosser X2 3W 10 km/h	5707299MCX2-3W106A
Mini Crosser X2 3W 13 km/h	5707299MCX2-3W136G
Mini Crosser X2 3W 15 km/h	5707299MCX2-3W156L
Mini Crosser X2 4W 10 km/h	5707299MCX2-4W106H
Mini Crosser X2 4W 13 km/h	5707299MCX2-4W136P
Mini Crosser X2 4W 15 km/h	5707299MCX2-4W156T
Mini Crosser X2 HD 4W 10 km/h	5707299MCX2-4WHD105S
Mini Crosser X2 CAB 10 km/h	5707299MCX2-CAB10KA
Mini Crosser X2 CAB 13 km/h	5707299MCX2-CAB13KG
Mini Crosser X2 CAB 15 km/h	5707299MCX2-CAB15KL



The Mini Crosser or parts (fx. batteries) af the Mini Crosser can, for a fee, be taken to the nearest dealer for disposal in accordance with current environmental regulations.

---

Manufacturer:	Medema A/S
Address:	Enggårdvej 7, DK-7400 Herning
Tel.	+45 7010 1755
Date: 16.03.2020	Signature:  Managing director Finn Dose

---

## Medema A/S Warranty

1:

There is a 2-year warranty, with the exception of worn parts such as tires, hoses, fuses, light bulbs, bushings and brake pads.

2:

If you want to make a claim for a part under the warranty, it must be intact. The warranty will be void if the product has been removed or appears to have been mishandled.

3:

There is a 5-year warranty against breakage and corrosion of the undercarriage.

4:

For the warranty to cover batteries, the charger used must be sold by Medema A/S.

The fabric, type and serial number must be indicated on the warranty specification, otherwise, warranty coverage may be denied.

5:

Items returned under a warranty claim must be suitably packaged to prevent damage during transport. Items damaged during transport due to poor packaging will not be covered by the warranty.

6:

The warranty does not cover freight costs.


7:

The warranty requires annual inspection and maintenance of the Mini Crosser by authorised professionals.



## Control panel

Avoid subjecting the control panel to jarring and knocks. Take care when driving and avoid hitting obstacles.



The manufacturer accepts no liability in respect of the unauthorised opening, adjustment or modification of the control panel.



## User menu

Term	Description
Menu / information 	Press the button and a menu at the top of the display switches between "Date", "Time", "Complete km", "Complete running time", "Battery Voltage" Service "and" inclination ". "Slope" is optional, and appears only if it is engaged. Button Menu / information are also used to modify the user parameters. Access these parameters by holding the menu button for approx. 3 sec.
Key switch 	To start the vehicle: Turn the key to position (1). The first half second after the Mini Crosser is on, the control is making a safety check of the electrical system. If the accelerator is affected during this time, the Mini Crosser will not be able to run, before the key again has been turned at 0 and back to 1 again.
Speed selector 	The turtle indicates lowest speed range. 0-6 km / h. The hare indicates the highest speed range. Up to 15 km / h. Increase/decrease with + / - button. The icons turtle/hare can be turned on/off from the User menu.
Battery indicator 	The left side of the display shows battery level indicator. Indicates that after approx. ½ seconds, the battery state of charge. Provides a more accurate indication after approx. 1 minute drive. When both red, yellow and green box lights are the batteries fully charged. Can be divided into 10 or 3 boxes. When the view is down the bottom of the yellow batteries should be recharged as soon as possible. If there is only light in the red boxes or flashing the batteries must be charged immediately.
Trip meter 	TRIP button resets the trip meter. Can be used while driving.
Hand brake 	Works on the left rear wheel and should only be used as extra brake / emergency brake and parking brake. It can be blocked in the locked position. Also available as a foot brake.



Term	Description
<b>Accelerator</b>  Forw. / Backw.	Front arm activates slowly and the Mini Crosser will start running forward. The more press, the faster it will run. When the lever is released, the arm flips itself back to the starting position and Mini Crosser stops. Upon activation of the posterior arm, the Mini Crosser run backward. The Magnetic brake on the rear wheels will strike at standstill, corresponding to the parking brake on a car. With speed regulation, speed can also be regulated downhill. The engine will then act as a brake.
<b>Light switch</b> 	Turns on the front and rear lights. The key switch must however be turned to position 1 (drive).
<b>Hazard warning lights</b> 	Turns on all lamps at once. Also works when the key is removed, or turned to 0 (stop position).
<b>Indicator lights switch</b> 	Arrow left: lamp left side. Arrow Right: lamp right side. Activate the same button again to turn off flashing lights.
<b>Horn</b> 	Electric horn which can be programmed in volume in the User Menu. Activated by pressing the horn button.
<b>Charging socket</b> 	Turn off the Mini Crosser (key in position 0) during charging. Note that it is not possible to run while the batteries recharge. See also the section "Batteries and Charging."

Term	Description
<b>Extras</b>	
Anti-theft alarm 	(Extra) With this parameter set to ON, the anti-theft alarm is turned on every time you turn off the Mini Crosser. An activated alarm is turned off by turning the key to 1 (drive). If you have no opportunity to get to the Mini Crosser with the key, the alarm will stop after approx. 20 seconds. Shake the Mini Crosser again, the alarm will be activated again.
Tilt 	Tilt-symbols.
Tilt Alarm sideways 	By exceeding the preset value, the symbol flashes and the horn hoots, if the parameter is enabled.
Tilt Alarm forw./backw. 	By exceeding the preset value, the symbol illuminate and the horn hoots, if the parameter is enabled.
Overheating step 1 	Step 1: The symbol flashes and the speed is reduced to half power. Wait for 3-5 min and start again.
Overheating step 2 	Step 2: The symbol will illuminate and Mini Crosser stops. Wait 3-5 minutes and start again.



## Programming the User Menu

Access the menu by holding the Menu/information button for approx. 3 sec. Scroll up and down with the + / -button under the display. The active parameter is highlighted with yellow writing and blue background. Access the value of the selected parameter by pressing Enter. Change the value using the +/- button. Confirm with Enter and exit with the Menu/information button.

Parameter description	
Date Format	Choose between: ddmmyy - day/month/year mmddyy - month/day/year yymmdd - year/month/day
Temp. unit (Temp. unit is extra)	Choose between Celsius or Fahrenheit. Displays ambient temperature.
Limited speed (On/Off)	Limited speed On/Off. To edit this function you will be asked for a 4 digit code. From the factory this code is set to be 1234, but it can be altered by a service technician. Use the +/- button to each digit. Go to the next digit with the "Next" button. Confirm with "Enter" Turn this parameter On/Off – Confirm with "Enter".
Limited speed (value)	Limited speed - value. To edit this function you will be asked for a 4 digit code. From the factory this code is set to be 1234, but it can be altered by a service technician. Use the +/- button to set % value, that you want the Mini Crosser's max speed reduced to. Move in increments of 5%.
Backlight (value)	The displays backlight can be changed in increments of 5%. Typically used in winter or when driving in darkness, where the intense light from the display may seem annoying.
Backlight auto (On/Off)	Selecting "On" reduced intensity of the backlight automatically when darkness falls or when driving into a tunnel or similar. Light sensor sits just above the light switch. See the Control panel.
Backlight threshold	Here max. light intensity is shown in%. Move in increments of 5%.
Reverse Buzzer (Off/ Beep/Buzz)	Same warning horn as it is known from trucks in reverse gear. Choose from "Off", "Beep" - low horns, or "Buzzer" - sharp horns.
Keyboard sound (On/Off)	With ON / OFF select whether to be acknowledged with a little beep when you press the contacts on the dashboard. These are: flashing, lights, hazard, menu, arrows and MENU keys.
Blinker sound (Off/ Beep/Buzz)	Choose whether you want a sound when flashing lights on the Mini Crosser is on. Just as we know it from a car. You can select "Off", "Beep" - low horns, or "Buzzer" - sharp horns.
Clock	Set time and date using the up / down with arrows. Moving to the next digit by pressing the "next" button. Quit with the "Enter"



<b>Parameter description</b>	
Hazard enabled (On/Off)	By default hazard (emergency lights) is operable even if the Mini Crosser is switched off and the key is removed. If you wish the hazard not be activated with the Mini Crosser turned off, you should select "Off." here.
Alarm enabled (On/Off) Extra	With this switch "On", the burglar alarm is turned on every time you turn off the Mini Crosser. The small lamp next to the "Trip meter" will flash a few seconds interval. An activated alarm is turned off by switching the key on the Mini Crosser. If you have no opportunity to get to the Mini Crosser with the key, the alarm will switch off after approx. 20th seconds. Shake / move the Mini Crosser again, the alarm will be activated again.
Tilt Present (On/Off) Extra	With this parameter set to "On", will turn the tilt icons to red and blinking, and there will be a whining tone (if enabled) if you are running on a slope that is steeper than allowed.
P&G fault log	Here are the faults that P & G engine management has registered. The system can record 8 different types of faults. Each fault can be recorded up to 30 times. The newest registered fault is written at the top of the list.  They are shown as follows: [1502] 2 None None None None None None None  In this case, the fault 1502 appeared twice. If you press ENTER on the fault you will get an explanatory text. In this case, "Solenoid brake fault"  None means that there have not been other faults.  In case of fault on the Mini Crosser, it will be a great help if the fault type can be given to the Mini Crosser or his representative during troubleshooting.

Temperature sensor, alarm system and tilt alarm are built into the same box that can be acquired as an option for the Mini Crosser X2.

## Preparations / Adjustments prior to use

### Adjusting the height of the seat

Lift both armrests up, and fold the seatback. Release the handle so the seat can turn. Turn a little and lift the seat off.

Make sure you keep your back straight when lifting the seat, which is very heavy.



*Lift the seat off the seat tube.*

## Hight adjustment seat post standard



*Loosen the counter nut.  
Use spanner, 17 mm.*



*Adjust the seat post to the desired position. The seat post is marked with a ring at each centimetre.*



*Be aware that the black line is holding its position after movement, so the seat is straight in front of the steering.*

*Tighten the screw, here after the counter nut.  
Mount the seat. Adjust the lining if necessary.*


## Hight adjustment seat post with position bolt (option)



*The release button pressed in. Press the button out to release the seat tube.*



*Release button pressed out. Now the seat tube can be moved up/down to the height you wish. Press the release button again and make sure it is fitted in one of the 5 holes in the seat tube.*



## Electric seat adjustment

The Mini Crosser can be fitted with electric seat adjustment as an optional extra.

To raise the seat, press the switch up. To lower the seat, press the switch down. If the switch is released, the seat will stop automatically. (See figure below.)



For safety reasons, a switch has been incorporated that reduces the speed by 50% when the seat is raised more than 7.5 cm.



*Electric seat adjustment. If the switch is pressed up, the seat is raised. If the switch is pressed down, the seat is lowered.*


### IMPORTANT!



The Mini Crosser is most stable when the seat is in its lowest position. Always drive carefully when the seat is raised. Never use the seat adjustment when driving on an uneven surface or in hilly terrain.



Take extra care when lowering the seat on a Mini Crosser using electric seat adjustment. Make sure that nothing is trapped in the space between the seat and the chassis.



*Avoid trapping anything when lowering the seat.*

---

## Seat rotation

Pull the release lever back. The seat can be rotated 90° to either side. When the lever is released, it engages with the seat and holds it in place at 45° intervals.

Other seats that can be supplied for the Mini Crosser work on similar principles. The release lever is normally mounted on the right, but can be put on the left if so wished.



*Release lever for seat rotation. Release lever for seat forward/back.*

---

## Steering column

Can be adjusted forward/back with the release lever. Pull down on the lever and pull the handlebars closer for a good driving position. Use the lever again and push the steering column forward to make it easier to get out.

The height of the steering column can be adjusted approx. 11 cm up/down. First remove the rubber plug covering the Allen screw. Adjust the height using a 4 mm Allen key.

This applies to both the 3W and the 4W model. Remember to retighten properly after adjusting.



Adjusting the height of the handlebars. Applies to both the 3W and the 4W model.

Lever for adjusting the angle of the handlebars




Adjusting the height of the handlebars. Applies to both the 3W and the 4W model.

Allen screw for height adjustment

## Serial number

All vehicles have a serial number plate showing the year of production and serial number. The same serial number can also be found on page two of this manual.

Please quote this number when making inquiries about servicing, spare parts, etc.



Position of serial number plate on vehicle.

## Driving the Mini Crosser X2

### Getting in and out

It is important to learn a safe technique for getting in and out of the Mini Crosser.

In general the following method should be followed:

- Make sure that the Mini Crosser X2 is off (switch turned to 0) when getting in and out, otherwise the Mini Crosser could start if the accelerator was touched inadvertently.
- Make sure that the brake is on. (Lever for disengaging motor in top position.)
- Put the steering column in vertical position.
- If necessary, turn the seat through 45° or 90° and make sure that it is locked in position (clicked into place).
- If necessary, raise the armrest.

For some users the assistance of an attendant can be recommended. The attendant should:

- Take care not to injure him/herself when lifting/lowering/supporting the user.
- Make sure that the Mini Crosser is stable and unable to move. Turn off the Mini Crosser and check that the brake is on and the seat has been rotated until it clicks into place at either 45° or 90°.
- Make sure that the seat the user is being moved to is stable.

#### IMPORTANT!



The Mini Crosser will turn itself off automatically after it has been stationary for 10 minutes even if the key has been turned to driving position. The battery indicator flashes with 6 lamps at a rate of about 3 seconds.

To restart the vehicle, the key must be turned to stop position (0) and then to driving position (1).



*Turn the Mini Crosser off, return the steering column to upright position, rotate the seat and raise the armrest.*

## General safety advice

Make sure that the backrest is upright and the seat is as low as possible.

Positioning belts are recommended if the user is unable to maintain a good driving posture independently.

Adjust your driving to road conditions. Take light, traffic and weather into account. Be particularly careful when driving in the dark or in bad weather, such as rain or snow. Avoid driving on inclines with poor surfaces, such as: snow, ice, new-mown grass, wet grass and wet leaves.



Never drive when under the influence. This applies not only to alcohol, but also to drugs and medicines.

Reduce speed immediately if you feel you are losing control.

Always use the indicators when changing direction.

Check that lights and indicators are working before driving off. Use your lights when driving after lighting-up time.

As far as possible, grip the handlebars firmly with both hands.



Take care not to have anything in the basket at the front that might inadvertently operate the accelerator.



**WARNING!** Do not lower the handlebars so far that the accelerator can hit you on the leg when you turn the vehicle and so be operated inadvertently. If the handlebars need to be very low, a twist grip accelerator is recommended. This is particularly relevant if leg supports are being used.



**ALWAYS** switch the Mini Crosser off when it is not in use. Turn the key to 0.

## Driving

Even though the Mini Crosser is very stable, it can tip over. Avoid sudden changes of speed and direction when travelling at high speed, on poor surfaces and, not least, on slopes. So be extra careful in following the driving tips given below.

Anti-tilt wheels are recommended for driving in very hilly terrain. (Optional extra)

New users are urged to practise the following in an area where there is no other traffic:

- Set the Mini Crosser to low speed. Drive forwards and backwards. Gradually turn the speed selector up and feel the change in the speed of the Mini Crosser.
- Practise starting and braking. Get used to the Mini Crosser's response time.
- Practise driving in a narrow space, similar to inside a shop or through a door.
- Practise turning, and get a sense of how much space is required. Always drive slowly when turning. Practise reversing too.
- Practise cornering and driving over obstacles and on slopes. Always drive straight up/down kerbs and ramps. Never at an angle. See the illustrations on the following pages.
- Try braking at different speeds and notice the stopping distances.
- If possible, try driving on different surfaces (road, grass and gravel).
- Practise assessing how far you can drive on a single battery charge. Note how quickly the battery indicator changes from green to yellow to red.

### Note!



The driving distance of the Mini Crosser will be reduced when driving in hilly areas, into a head wind, in cold weather and with low tyre pressure.

## Traffic regulations

The traffic legislation for Mini Crossers varies from country to country. Before starting to use the vehicle outdoors, it is the user's responsibility to familiarise him/herself with the relevant legislation.

---

## Lap belt



*Lap belt*

If there is a need for it you can, as an accessory, mount a lap belt or harness belt on MC 1124.

The belt is designed to stay safe to use for at least 10 years.

## Electromagnetic compatibility

The Mini Crosser is EMC tested according to EN 60601-1-2 and meets the requirements for Mini Crosser used in an environment with electromagnetic noise. There may, however, be rare situations in which electromagnetic noise can affect the Mini Crosser. Sources of such noise include radio and television stations, amateur radio transmitters and mobile phones.



If the Mini Crosser starts making involuntary movements or if the brakes are released, turn the Mini Crosser off as soon as it is safe to do so. In certain circumstances a Mini Crosser can set off shop alarms.

## When driving in traffic...

Be particularly aware of the following when driving in traffic:

- The Mini Crosser is a low vehicle and not always easy for other road users to see. Make quite sure that other road users have seen you before driving onto the highway.
- Keep an eye on traffic behind you. Keep well over to the side of the road when driving on busy roads.
- Turning right and left at crossroads. Be aware of cyclists and pedestrians. Follow the rules of the road for cyclists.
- How quickly things are happening. How long do the lights stay green? How quickly are cars approaching? etc.

## Specific driving situations


### Up kerbs

- Stop at right angles to the kerbstone about 5-10 cm away from it. Keep an eye on other road users.
- Lean forwards.
- Accelerate moderately so that your vehicle can overcome the obstacle. Do not stop halfway, but reduce speed once the vehicle is up.
- If the kerb is too high, do not try again, but find an alternative route.




### Down kerbs

- Lean back.
- If you are driving onto a road with traffic, keep an eye on other road users.
- Drive forwards and down the kerb at low speed. Make sure that your anti-tilt wheels (if fitted) do not catch on the edge.




## Up a ramp/hill

- There is a risk of tipping over backwards if the seat is pushed back when you start driving up a slope, e.g. a ramp.
- Pull the seat forward! Check that any ramp is stable.
- Lean forwards.
- Accelerate moderately so that your vehicle can overcome the obstacle. Do not stop halfway. Reduce speed once the vehicle is up. If you need to start on a hill, accelerate slowly so as not to tip over backwards.



## Down a ramp/hill

- Check that any ramp is stable.
- Lean back.
- Drive slowly down. Avoid stopping midway on short, steep slopes. On long hills, it is advisable to stop every now and again if you feel your speed is getting too high.



### Warning!



Be aware that the stopping distance can be significantly longer, down hill, than on level ground.

## Across a slope

- Lean into the slope.
  - Avoid sudden and sharp movements. This is particularly relevant when reversing.
  - Always drive at low speed.
- 

## Long hills/difficult ground

The Mini Crosser is at risk of overheating on very long and steep hills or on very soft ground, possibly also combined with high user weight.

To protect the Mini Crosser motor from overheating, there is a built-in thermo switch, which initially sets the Mini Crosser to half speed.

However, if you carry on moving over difficult ground, the Mini Crosser will at some stage stop completely. The Mini Crosser must be left to cool down for 3-5 minutes before it can start again.

To reset the fault, switch off the Mini Crosser then turn it on again.

If the Mini Crosser has not had long enough to cool down when it is restarted, it will initially only run at half speed.

**Note:**

The situation described above will never happen in normal use. It only happens if the conditions are extremely challenging.

## Anti-tilt wheels / stabilisers

The Mini Crosser is a very stable vehicle. HOWEVER, in the case of incorrect weight distribution or careless driving there is a risk of tipping over.

We therefore recommend fitting anti-tilt wheels in such circumstances. (See picture below). Contact Medema for more info. Find contact information on page two in this manual.



*Anti-tilt wheels*

---

## Cleaning

Clean the Mini Crosser with a damp cloth. If necessary, wipe dry with a chamois leather.

Wipe the covers dry and polish with car wax.



**IMPORTANT!** Never use high-pressure cleaner or hose, as it could damage the Mini Crosser's electronics.

## General care and maintenance

A Mini Crosser X2 does not require much maintenance. It should be kept in a generally good condition, however. The following should be checked regularly:

- Tyre pressure (if pneumatic tyres are fitted)
- Tyre wear
- Keep the control panel, the charging socket and the electronics box under the seat dry.
- Battery charging



Never wash the Mini Crosser with a high-pressure cleaner or direct water jet! This could damage the Mini Crosser's electronics.

To keep the Mini Crosser in good condition safety-wise, we recommend the following regular checks:

Daily: (User)

- Test the indicators and driving lights before using the Mini Crosser in the dark or poor visibility.

Every three months: (User)

Test the brakes and motor disengagement

With the disengagement lever up, it must not be possible to push the Mini Crosser.

Test the brake disengagement function

When the brake disengagement lever is down, the battery indicator should flash to show an error if the Mini Crosser is turned on. In this case the Mini Crosser must not be able to move when the accelerator is activated.

Test the hand brake

Apply the hand brake for a couple of seconds at low speed. This will ensure that the lever arm and brake shoes do not seize up.

Lubricate the lever arm on the brake hub with acid-free oil - left-hand rear wheel.

### Service (Technician)

The Mini Crosser X2 is designed for safe travel for at least 10 years, up to a max. of 5,000 hours, provided it is serviced and safety-checked every third year, corresponding to 1500 hours of operation. The service must be carried out by an authorised workshop.



**IMPORTANT!** For safety reasons it is of the utmost importance that the servicing and safety check intervals are complied with, as this minimises the risk of brake failure and short-circuits in the wiring, which could generate heat and cause a fire.

(For further information see the Service Manual.)

---

### Insurance

In the eyes of the law a Mini Crosser X2 with a maximum speed of 15 km/h is a cycle, so separate insurance is not required.

Most contents/home insurance policies include third-party liability insurance for cyclists and so also cover Mini Crosser X2 users.

We recommend that you talk to your insurance company about this when the vehicle is delivered. If necessary, comprehensive insurance will have to be taken out separately.

## Batteries

The Mini Crosser uses sealed, maintenance-free GEL or AGM batteries.

They do not generate gas and do not have to be topped up with water.

---

## Battery weight

56 Ah = 21 kg

85 Ah = 27 kg

---

## Charging

Please NOTE that the Mini Crosser can be equipped with several types of charger (ask your dealer for information on the various types).



**IMPORTANT!** Only ever use a charger designed for charging dry maintenance-free batteries. The max. charging current is 12 A.

Never use charging devices other than those supplied from the factory without first contacting the dealer.

If charging is to take place outdoors, an enclosed charger without a fan should be chosen.

The battery indicator shows how much power is available to the Mini Crosser.

- Red, yellow and green indicate that the batteries are fully charged.
- Red and yellow indicate that the batteries will soon need recharging.
- Red indicates that the batteries need to be recharged as soon as possible, otherwise the Mini Crosser will cut out.

The battery manufacturer recommends that the batteries are charged at a temperature of + 10° to +30° C in order to achieve a charging time as specified in the section Technical data.

---

The charging time will be extended by approximately 60% at a temperature of +5° C compared to a temperature of +20° C. This is because it is chemically more difficult for the battery to absorb the current.

Avoid deep discharging. It is recommended to charge the Mini Crosser in a heated room. If it is not possible every day, then at least once a week.

New batteries only achieve full capacity after about 20 charge/discharge cycles.

Be aware that the capacity of the battery decreases with time, as well as at low temperatures. The battery capacity at -10°C is half of the capacity at +20°C.



When driving in hilly terrain, on slopes and up/down curbs, the distance that can be driven, before recharging the battery, is reduced.



The Mini Crosser should be charged when the vehicle is not in use. The type of charger supplied by the factory works in a way that it automatically switches over to trickle charging (very little electricity consumption) when the batteries are fully charged.



It is not allowed to place the charger on the seat during charging.

The charger will flash until it is finished. Then the indicator on the charger will be constantly lit.

The charger CANNOT overcharge the batteries! So let the charger stay connected until the Mini Crosser is used again.

**Note!**



Since the Mini Crosser also uses some power even when it is turned off and the ignition key is turned to 0, it is recommended that it is always connected to the charger when not in use.

## Battery disposal

Used batteries must be disposed of through your supplier or at a recycling centre.

Take care when handling any leaky batteries, as they contain corrosive acid.

INFO! New batteries can be purchased from Medema A/S.

---

## Standby power

The X2 Mini Crosser is equipped with an advanced display solution. The system requires that there is always a small standby power consumption of 70 mA.

If you do not make sure that the Mini Crosser is set to charge at appropriate intervals, the batteries will fully discharge over time.

For this reason, we recommend that the Mini Crosser is always set to charge when it is not being used.

Below is a recommended schedule of how many days before a brand new battery is 100% discharged. The discharge time depends on factors such as the ambient temperature, age and how many Ah the battery has been rated in C20.

Ah in C20	100% discharged after
56 Ah	33 døgn
85 Ah	47 days

The calculations in the table is only guiding!

### Note




If the battery is 100% discharged, it is not possible for the charger to start charging the battery.

There is no warranty on batteries that have been damaged as a result of deep discharging.

If you are not using the Mini Crosser for a longer period of time, for example during winter storage, you can choose to disconnect the one pole to the fully charged batteries. This way there will be no consumption of standby power.

---


It is important to fit the batteries correctly. The battery terminals are marked +/- . They must be fitted as shown in the sketch below. Make sure that the terminals are properly tighten. For the same reason there must not be any burrs on the cable terminals.



Be aware that the Mini Crosser can varies types of chargers. Contact your dealer for more information about the different types.

Do NEVER use other chargers than the one from the factory without contacting your dealer first.

### Polarity of charging plug



NEUTRIK NC3MX charging plug



Connect the charging plug to the 3-pin socket on the steering column. The charging socket is located under the protective cover.

### Note



If the battery is 100% discharged, it is not possible for the charger to start charging the battery.

There is no warranty on batteries that have been damaged as a result of deep discharging.

If you are not using the Mini Crosser for a longer period of time, for example during winter storage, you can choose to disconnect the one pole to the fully charged batteries. This way there will be no consumption of standby power.

---

## Storage

The Mini Crosser should be stored and charged under cover preferably at temperatures above 0°C.



Note!

The charger must be kept dry, but should not be covered when in use.

In the case of long-term storage we recommend covering the Mini Crosser to protect it from dust, rain and sunlight.

## Changing the wheels

If you get a puncture in one of the pneumatic tyres or if a tyre is so badly worn that it needs to be replaced, follow the instructions below.

Tyres and inner tubes can be purchased from the authorised dealer who supplied the Mini Crosser.

The Mini Crosser must be TURNED OFF before you start.



### Changing the wheels on the 4W model

Remove the hubcap.

5 mm Allen key

- Undo the five bolts.
- Take the wheel off.
- When the wheel is put back on, the spring washers must be refitted between the wheel rim and bolts.

The bolts must be done up tightly.



Remove the valve cap and use a screwdriver or similar to open the valve so that the air can be released.



### Important!

There is a risk of explosion of the wheel, if the two rims are being taken apart with air in the tire.

#### REMEMBER!



- to let all the air out before taking the wheel apart to repair a puncture
- to secure the bolts with spring washers



Remove the flange with the 5 screws (5 mm Allen key).



Replace or patch the tube. Ensure that there are no foreign objects in the tyre before the tube is replaced.

Pump air into the tube so that it is positioned correctly in the tyre, but do not fill it up completely yet.



In this way the tube will not get jammed, when the flange is mounted again.

Put the flange back on.

Pump up the tyre to the correct pressure. (See technical data)



Put the wheel onto the Mini Crosser again.

**REMEMBER!**  
The spring washers between the screws and the wheel rim.



### Changing the wheels on the 3W model

Rear wheels: Take off in the same way as described in the section Changing the wheels on the 4W model.

Front wheels:  
17 mm fork spanner  
6 mm Allen key  
5 mm Allen key



Unscrew on both sides.



Remove the centre axle by unscrewing the 5 screws here.



The centre axle removed.



Remove the valve cap and use a screwdriver or similar to open the valve so that the air can be released.



**REMEMBER!**

- to let all the air out before taking the wheel apart to repair a puncture
- to secure the bolts with spring washers



**Important!**

There is a risk of explosion of the wheel, if the two rims are being taken apart with air in the tire.



Remove the flange with the 5 screws (5 mm Allen key).



Replace or patch the tube. Ensure that there are no foreign objects in the tyre before the tube is replaced.

Pump air into the tube so that it is positioned correctly in the tyre, but do not fill it up completely yet.

In this way the tube will not get jammed, when the flange is mounted again.

Put the flange back on.

Pump up the tyre to the correct pressure. (See technical data)



Put the centre axle on again.




Put the wheel onto the Mini Crosser again.

## Fuses

**The Mini Crosser has the following protection systems:**

- As a safeguard against overheating There are two switches are integrated in the engine. By incipient overheating speed is reduced to half power, and by prolonged overheating the Mini Crosser will stop. After cooling for 3 to 5 minutes, the Mini Crosser is able to reach full speed and traction.
- The control fuse protects against mains faults. It is located under the rear cover.
- The main fuse protects against short-circuits in the main current circuit. The fuses are located under the rear cover behind the batteries. Fuse type DIN 2581 - 100A.
- If the ignition key is turned at the same time as the accelerator is operated, the vehicle will not move off for safety reasons.
- The lights and horn are protected by electronic fuses, which protect against any short-circuiting that may occur. To prevent accidental short-circuiting when a bulb is changed, the Mini Crosser must be turned off when the new bulb is fitted and then turned on again afterwards.



*Take the rear cover off. The plastic cover can be removed by squeezing the sides. Now the fuses can be replaced.*

## Brakes

There are four braking systems on the Mini Crosser:

- Motor brake - adjusts vehicle speed also when going downhill.
- Magnetic brake - the magnetic brake is automatic and engages when the Mini Crosser stops. In an emergency, the Mini Crosser can be stopped instantaneously by turning the key switch. Please note that this will cause very sharp braking. The brake must never be disengaged mechanically using the disengagement lever on a slope. This function is only designed for use when pushing the Mini Crosser on a flat road.
- Electric safety brake - if the brake is somehow disengaged on a slope/hill, the Mini Crosser will brake automatically when it reaches a certain speed. There is an electric safety feature in the control system, which works even if the battery is disconnected. This is also the reason why the Mini Crosser cannot be towed at more than 5 km/h. See the section about towing.
- Hand brake - intended as an emergency brake and parking brake. It must be operated with caution when driving in slippery conditions and downhill.



*When using the handbrake as a parking brake, lock it in braking position by pressing the button in while applying the brake.  
To release the brake, press the button again.*

## Disengagement

### Manual

The manual disengagement lever is placed underneath the back cover. Follow this procedure to use it.

- Turn the key to (0) position.
- Push the disengagement lever down.  
The motor brake is now disengaged and the vehicle can be pushed or towed, but not drive itself.

### Electronic

The yellow electronic disengagement button is placed on the back of the vehicle. This only works when the scooter is turned on.



### NOTE!

**Don't ever disengage on sloping terrain.**

If the brake is somehow disengaged on a slope/hill, the Mini Crosser will brake automatically when it reaches a certain speed. There is an electric safety feature in the control system, which works even if the battery is disconnected. This is also the reason why the Mini Crosser cannot be towed at more than 5 km/h. See the section about towing.

**Once the motor brake has been disengaged, the Mini Crosser can only be stopped with the hand brake.**



*Push the disengagement lever down to disengage (only hand brake works) and push up to reactivate the motor (normal driving now possible).*



*Disengagement lever*



*Electronic disengagement. Works only when the scooter is turned on.*

*Disengagement button.*

---

## Transporting by motor vehicle

The Mini Crosser must always be restrained and the hand brake locked during transport in a motor vehicle or trailer.

Avoid lifting by the seat, covers, handlebars and armrests

If you just need to lift the Mini Crosser slightly, take hold of it between the rear lights and by the front bumper.

**Important!**

If you drop the Mini Crosser from a height of half a metre or more, there is a risk that the gears in the transaxle will be destroyed.

Secure it in the vehicle with belts attached to the two eyes at the front and two at the back. All the eyes are marked in yellow. See the section entitled "Securing to vehicle floor with belts".

## Securing to vehicle floor with belts


Dahl Engineering belt set for securing in motor vehicles.

ALWAYS use four belts at the back and two at the front.

The belts must always be attached to approved fittings in the vehicle and the four eyes welded to the Mini Crosser.

The belts MUST be attached within the angles shown in the picture for optimum security.








For transport in an estate car, the seat can be folded and the handlebar folded down. This reduces the maximum height to 70 cm.

The Mini Crosser can be used as a seat during transport in a van or bus, provided it is securely anchored to the vehicle with approved four-point belts attached to the restraint points provided on the Mini Crosser.

The Mini Crosser's restraint points have been tested and approved in accordance with ISO 7176-19.

The user must also always be independently restrained in the actual motor vehicle in accordance with traffic legislation rules.

### Example



#### **Restraining the passenger with a static 3-point seat belt:**

Secure to the rearmost retractors.

The shoulder belt must rest against the collar bone and fall diagonally to the hip, where it is secured.

Tighten the belt by pulling

on the loose strap. Undo it again by lifting the buckle. This is the same as on an aircraft.



Retractor with belt



Male and female parts of belt done up



Remember to turn the Mini Crosser off during transport. Turn the key to 0.

However, if at all possible, we recommend that the user occupies one of the seats in the motor vehicle. All other things being equal, this is safer.

## Transporting by plane

If the Mini Crosser is to be transported by plane, the airlines require:

- the batteries to be flight-approved
- the air to be let out of the tyres
- the battery leads to be disconnected (not always, but frequently)

The seat and cover have to be removed to disconnect the battery leads.



*Lift the armrests up, and fold the seat completely. Release the seat turn - turn the seat a little and lift it off.*



*Remove the thumbscrew and remove the battery cover.*



*Disconnect the (+) pole.*

A battery declaration for air travel can be requisitioned from Medema A/S.home page.

<https://www.medema.dk/tjenester/service-reparation/flycertifikat/>

---

## Towing

If you should be unfortunate enough to break down, the Mini Crosser can be towed or pushed. The Mini Crosser must always be turned off and the motor brake disengaged during towing. See the section on Brakes.




If the Mini Crosser is to be towed, secure a rope to the tow fitting on the front - marked with a yellow "hook mark". Do not tow faster than 5 km/h. The Mini Crosser will generate electricity when it is towed, with the motor acting as a dynamo. If it is towed at more than 5 km/h, there is a risk of the motor generating enough electricity to damage the Mini Crosser and, in the worst case, cause a fire.

The Mini Crosser will try to brake if it is towed at more than 5 km/h.


---

## Dimensioned drawing, Mini Crosser X2 3W



X2+ : Equipped with extra large batteries, the foot space will be reduced.

## Dimensioned drawing, Mini Crosser X2 4W



X2 : Equipped with extra large batteries, the foot space will be reduced.

## Introduction to the Ergo2 seat

The Ergo2 seat is designed to stay safe to use for at least 10 years.



### Lever for rotating the seat

The lever must be pulled back to rotate the seat. The seat can then be rotated to each side, locking at each 45°.

The lever is spring-loaded, and the seat is locked automatically when the lever is released. This lever is located on the right side as standard, but can also be positioned on the left side. When the lever is located on the left-hand side, it must be pushed forward in order to rotate the seat instead of pulling back.



### Out / in adjustment of the lever for rotating the seat

Lift the seat off the vehicle.

Loosen the two Allen screws and the lever can now be adjusted out and in to the desired position.



### Placement of lever for rotating the seat on the left-hand side

Remove the two Allen keys and pull the lever out. Insert the lever from the left-hand side and tighten the Allen screws.

When installing the lever on the left-hand side, the lever must be pushed forward to rotate the seat..



#### Mount the seat again

In order to ensure that the seat returns to the correct position, the lever for rotating the seat must be released in order to place the seat.



#### Lever for fwd/bw adjustment of the seat.

Pull the lever up to release the seat on the slide rail.

Then the seat can be moved forward or backward as desired with 200 mm of travel.

When the lever is released, the seat will automatically lock into place in the closest position.



#### Height adjustment of armrest

Unzip the zipper on the side of the backrest and the backrest itself.



Unscrew the Allen screw and the armrest can be pushed up or down as needed.  
It can be adjusted 140 mm.



#### Width adjustment of armrest

Each armrest can be adjusted 25 mm on each side.  
Loosen the Allen screw and the armrest can be adjusted longitudinally.



#### Adjusting the angle of the armrests

The adjustment screw makes it possible for the armrest to be adjusted 60°.

The armrest can be tilted up to facilitate entry and exit.



#### Adjusting the angle of the backrest.

The angle of the backrest can be adjusted 45° backward and 90° forward. This is done by pulling the lever on the right-hand side of the seat.



Backrest tilted 45° backward.



Backrest tilted 90° forward.

This is why the seat does not necessarily need to be removed during transport, e.g. in a car.



**Backrest forward / back.**

Loosen the specified screws on both sides.



The depth of the seat can now be adjusted by sliding the seatback forward and back.

Shown here with 320 mm seat depth.

The seatback can then be moved backward to the edge of the rail and forward to the desired position. Tighten the screws after adjusting.



Shown here with 550 mm seat depth



#### Height adjustment of headrest.

Press the button and the headrest can be raised and lowered as needed.



#### Adjustment of the headrest forward and backward.

The headrest can be tilted forward and backward as needed.

## Basket in front



Mount the basket on the brackets (Click on) and now it is ready for use.

Baskets are part of a wide range of accessories. Contact your local dealer or Medema A/S. See contact information on page two in this manual.

## Basket on seatback



**Mounting of basket on the seat.  
(Optional accessory)**

Complete mounting kit for basket.  
Two brackets and four Allen screws.



Unzip the zipper and position the brackets in front of the two predrilled holes.



Mount the basket on the brackets and now it is ready for use.  
Remember to insert a locking split after mounting.

Baskets are part of a wide range of accessories. Contact your local dealer or Medema A/S. See contact information on page two in this manual.

## Introduction to the Eblo seat



### The lever for turning the seat.

Pull the lever up to release the seat. The seat can then be rotated 90° to each side, locking at each 45°.

The lever is spring-loaded, and the seat is locked automatically when the lever is released.

This lever is located on the right side as standard, but can also be positioned on the left side.



### Lever for fore/aft adjustment of the seat.

Pull the lever up to release the seat on the slide rail. Then the seat can be moved forward or backward as you wish. When the lever is released, the seat will automatically lock into place

in the closest position.

There is a stop on the front and the back of the slide rail.



### Adjusting the angle of the armrests

The angle of the armrests can be adjusted by turning this screw.



### Adjusting the angle of the backrest

The angle of the backrest can be adjusted approximately 140°. This is done by lifting this lever.



### Adjusting the lumbar support:

The lumbar support can be adjusted by turning the handle counter-clockwise.



### Headrest:

The headrest can be adjusted up/down in steps.

---

## Flame resistance

The Mini Crosser seat's flame resistance has been tested in accordance with DS/EN 1021-2:2014 Furniture - Assessment of the ignitability of upholstered furniture - Part 2: Ignition source match flame equivalent.

### Warning!



The seat may become very hot if exposed to direct sunlight. Similarly, the seat will become very cold if it is exposed to cold temperatures, e.g., frost.

## Troubleshooting

The following is a list of various problems that, in our experience, may occur. The list gives possible causes and remedies.

Problem	Possible causes	Remedy
The Mini Crosser will not go.  The battery indicator is not lit.	The key has not been turned to start.  The batteries are completely flat. The control fuse has blown. The main fuses have blown.	Turn the key and wait 5 sec. before activating the accelerator.  Charge the batteries.  Change the fuse.  Contact supplier.
The Mini Crosser will not go, but the battery indicator is lit.	The Mini Crosser has been overloaded.  The hand brake is on. There is a fault in the electronics. The batteries are flat. The charging plug has not been removed.	Wait approx. 1 min. before trying again. The vehicle must be turned off (see section on Fuses).  Release the hand brake. Contact supplier.  Contact supplier. Remove the charging plug.
Mini Crosser drives unevenly, choppy while driving.	Can be caused by poor connection of electricity.	Turn off the Mini Crosser immediately and seek out an authorised workshop. If you continue driving, heat can be generated in the poor connection resulting in a risk of fire.
Mini Crosser drives unevenly, choppy while driving.	Can be caused by poor connection of electricity.	Turn off the Mini Crosser immediately and seek out an authorised workshop. If you continue driving, heat can be generated in the poor connection resulting in a risk of fire.
The driving speed is too low.	The speed selector is on slow.  The electronics are overloaded. There is too little air in the tyres.	Change to a faster speed.  Stop and wait 3-5 minutes before starting. Pump the tyres up to the right pressure.
The driving distance per charge is too short.	There is a problem with the batteries. Low temperature.  There is a problem with the charger. There is too little air in the tyres. The charging method is wrong.	Charge the batteries and check that the green lamp on the charger lights up before driving off.  Contact supplier.  Pump the tyres up to the right pressure. Read the section on Charging in the User Manual.

Problem	Possible causes	Remedy
The charging lamp on the charger does not light up when the charger is connected to the mains and the Mini Crosser.	No power to the switch. Fault in cable. Fault in charger.	Turn the switch on. Contact supplier. Read the operating instructions for the charger. Contact supplier.
The "ready" lamp on the charger does not light up even though the charger has been on for 10-12 hours.	There has been a power cut.  The charger is doing a top-up charge.  There is a problem with the batteries.  There is a fault in the charging plug for the Mini Crosser X2.	Reconnect the charger and repeat the charging process. Check again half an hour later. Contact supplier.   Push the charging plug all the way in and repeat the charging process. Read the operating instructions for the charger.
The "ready" lamp on the charger lights up even when partly discharged batteries are connected.	The fuse in the charger has blown.  The switch in the charging plug is malfunctioning.	Contact supplier.  Contact suppliers - read the operating instructions for the charger.
The charger lamp is showing an error.	The charging plug has not been inserted or there is a mains fault.  The battery voltage is too low for charging to start.	Push the charger plug in or contact the supplier.  Read the operating instructions for the charger - or contact the supplier.
Thermometer symbol is half-red and flashes. The Mini Crosser is running at half speed.	The motor is overheating and has reached the limit of when the first safety switch responds.	Immediately pull over at a safe distance from other traffic and stop the Mini Crosser. Wait until the temperature icon disappears, ca. 3-5 min. Turn the Mini Crosser off and on again to continue at full speed.
Thermometer symbol is red and illuminated. The Mini Crosser has stopped.	The motor is overheating and has reached the limit for when the security switch shuts the motor off completely.	If the Mini Crosser has stopped at an inappropriate place in traffic, turn on the emergency lights. If possible disengage the Mini Crosser and push it away from traffic. Let Mini Crosser cool until the temperature icon disappears - approx. 3-5 min. Turn the Mini Crosser off and on again. Now it can run normally again.
Mini Crosser can not remember the time.	Battery on main circuit board has run out of power.	Contact service technician.

## Electronic faults

If there is an electronic fault, a number of lamps in the battery indicator will light up. The following table shows what they mean.

Lamps	Causes	Remedy
1 lamp	The batteries need charging or the connection to a battery is poor.	Check all connections between the controller and batteries. If these are fine, try charging the batteries
2 lamps	Poor connection to the motor.	Check the connection between the motor and controller. Contact supplier.
3 lamps	Short-circuit between the motor and a battery connection.	Contact supplier - say how many lamps are lit.
4 lamps	Not in use	
5 lamps	Not in use	
6 lamps	The S200 is prevented from driving. Inhibit 2 is active. This may be due to the battery charger being connected, the plug to the thermal switches being disconnected, a fault in the thermal switch or the Mini Crosser is overheating.  The Mini Crosser will turn itself off automatically after it has been stationary for 10 minutes. The battery indicator flashes with 6 lamps at a rate of about 3 seconds.	Stop the unit and wait 3-5 minutes before restarting. Turn the key to 0 and then to 1 to reset the fault.  Contact supplier.  To start X2 again, the key must be turned to position 0 and back to I.
7 lamps	Accelerator fault.	Contact supplier.
8 lamps	Controller fault.	Contact supplier.
9 lamps	Poor connection to motor brake.  Magnetic brake is disengaged.	Check the connections from brake to controller, or push the brake lever up.  Check that the vehicle is not disengaged.
10 lamps	The controller has been supplied with a high voltage in excess of 38 V. Usually seen in the case of a poor connection.	Check all connections from the batteries to the controller.
Running lights	Charger is connected. Remove charger.	Remove charger.
Running lights from the centre and out.	The accelerator has been activated during start up.	Turn the key back to 0 and to 1 to reset the fault.

## Technical data

Technical data	X2 3W	X2 4W
<b>General information:</b>		
Transport height without seat (Steering column folded down)	70 cm	70 cm
Total length: Total length incl. anti-tilt wheel: Total width:	135 cm 142 cm 66 cm	140 cm 148 cm 66 cm
Total weight incl. batteries and Ergo2 Std seat. (45 cm)	158,5 kg	169,5 kg
Weight without seat (Ergo Standard 45 cm).	133 kg	144 kg
Dynamic stability in all directions.	13° - 23%	13° - 23%
Kerb climbing	11 cm	11 cm
Max. speed Option 1 Option 2 Option 3	10 km/t 13 km/t 15 km/t	10 km/t 13 km/t 15 km/t
Braking distance 10 km/h 13 km/h 15 km/h	2,0 meter 2,8 meter 3,5 meter	2,0 meter 2,8 meter 3,5 meter
Controller	S-200	S-200
KW transaxle	0,7 kW	0,7 kW
Turning Circle / radius	265 cm / 132,5 cm	330 cm / 165 cm
3-point Turning Circle / radius	170 cm / 85 cm	190 cm / 95 m
Max user weight incl. accessories- standard	175 kg	175 kg
Max user weight incl. accessories HD version.	-----	250 kg
Classification, IP Mini Crosser Controller JK Medico charger	IPx4 IPx5 IP54	IPx4 IPx5 IP54
<b>Wheels</b>		
1503-1003 Wheel, model-X, 2,50-3,30-8". complete with rim and tyre.	41 psi / 2,8 bar 	41 psi / 2,8 bar 
1503-1114 13x5.00-6" ext. Ø325 mm Wheel Norway black - T, E, Nordic, MaxX, MaxX HD, M and X	59 psi / 4,1 bar 	59 psi / 4,1 bar 

<b>Technical data</b>	<b>X2 3W</b>	<b>X2 4W</b>
1503-1115 13x5.00-6" ext. Ø325 mm Wheel Norway black w/spikes - T, E, Nordic, MaxX, MaxX HD, M and X	59 psi / 4,1 bar 	59 psi / 4,1 bar 
1503-1336 13x3.00-8" ext. Ø340 mm Wheel black - T, M and X	51 psi / 3,5 bar 	51 psi / 3,5 bar 
1503-1273 13x3.00-8" ext. Ø340 mm Wheel black puncture free - T, M and X	PUR 	PUR 
1503-1012 3,50-8" ext. Ø370 mm Wheel, model X Used only as rear wheels and never with 15 km transaxle	2,8 	2,8 
Classification, ISO	Klasse C	Klasse C
<b>Seats:</b>		
Effective seat width Ergo2 child Ergo2 standard Ergo2 HD Eblo	35 cm 40, 45, 50 cm 60, 70 cm 50 cm	35 cm 40, 45, 50 cm 60, 70 cm 50 cm
Effective seat depth Ergo2 child Ergo2 standard + HD Eblo	20-43 cm 32-55 cm 43 cm	20-43 cm 32-55 cm 43 cm
Seat plane angle	3°	3°
Backrest height Ergo2 child Ergo2 standard + HD Eblo	44 cm 54 cm 52 cm	44 cm 54 cm 52 cm
Seat surface height from ground to front edge Ergo2 (child, standard + HD) Eblo	59 - 69 cm 61 - 71 cm	59 - 69 cm 61 - 71 cm
Seat surface height from footrest to front edge Ergo2 (child, standard + HD) Eblo	42 - 52 cm 44 - 54 cm	42 - 52 cm 44 - 54 cm
Backrest angle Ergo2 (child, standard + HD) Eblo	-90° til +48° -54° til +80°	-90° til +48° -54° til +80°
<b>Batteries:</b>		
56 Ah Batteries.	35 km (*)	35 km (*)

<b>Technical data</b>	<b>X2 3W</b>	<b>X2 4W</b>
85 Ah Batteries.	45 km (*)	45 km (*)
Battery type: Standard: Option:	2x12V / 56 Ah 2x12V / 85 Ah	2x12V / 56 Ah 2x12V / 85 Ah
Max battery measure i cm. 56 Ah 85 Ah	26,5 x 17 x 23 26 x 17,1 x 21,5	26,5 x 17 x 23 26 x 17,1 x 21,5
Battery weight pr. stk. 56 Ah 85 Ah	21 kg 27 kg	21 kg 27 kg
Energy consumption in kWh, when charging from "empty". 56 Ah 85 Ah	Ca. 1,5 kWh Ca. 1,5 kWh	Ca. 1,5 kWh Ca. 1,5 kWh
Charger, 24 V DC 56 Ah 85 Ah	6 - 10 A 6 - 10 A	6 - 10 A 6 - 10 A
Approx charging time at 20 ° C	8 hours	8 hours
<b>Lighting:</b>		
Headlight	LED	LED
Rear light	LED	LED
Blinkers	LED	LED
Standard colours Option 1 Option 2	Orange - metallic Sort - metallic	Orange - metallic Sort - metallic
<b>Noise:</b>		
Noice level	60db	60db
<b>The Mini Crosser X2 complies with the following standards:</b>		
The Mini Crosser has been tested for the requirements described in:		EN 12184
ISO 7176-15 Annex A		
a) requirements and test methods for static, impact and fatigue strengths (ISO7176-8)		Conforms
b) Power and control systems for electric wheelchairs, requirements and test methods. (ISO 7176-14)		Conforms
c) climatic test in accordance with ISO 7176-9		Conforms
<b>Miscellaneous</b>		
Front basket, max load	8 kg	8 kg
Rear basket, max load	15 kg	15 kg
Wheel bolt tighten max: Dry Greased with fat	12 Nm 6 Nm	12 Nm 6 Nm

(\*) Driving distance is depending on: temperature, wind, terrain, tyre pressure and user weight.

Maximum driving distance with new batteries at +20° on flat, firm surface  
Optimum battery capacity is reached after approx. 20 charges / discharges.



## Weight of the seats



This is our standard Ergo2 45 cm seat, the heaviest part of the X2 to remove. The label showing the seat's weight is located as shown above.

Seat model	Weight
Eblo seat 45 cm	19 kg
Ergo2 seat 35 cm	20 kg
Ergo2 seat 40 cm	26 kg
Ergo2 seat 45 cm	27 kg
Ergo2 seat 50 cm	29 kg
Ergo2 seat 60 cm	36 kg
Ergo2 seat 70 cm	37 kg

## Programming



NOTE! For safety reasons, modifications may only be made by trained personnel, such as Mini Crosser service engineers and consultants or authorised service personnel at mobility centres, etc.



**medema**gruppen